

System Amplifiers

DI-4.1000

High performance system amplifier for mobile and fixed installation, 4 × 1000 W, 2 U, 19"



Analog

AES/EBU

 Dante™

System Amplifiers DI-4.1000

The DI-4.1000 is a digital 4-channel amplifier Made in Germany. The DSP amplifiers developed and manufactured by Fohhn offer high power density and excellent sound. The amplifiers are designed for mobile sound systems and fixed installation. They provide all the essential features and almost limitless connectivity in terms of audio inputs. Whether AES/EBU, Dante or Analogue – they offer maximum flexibility thanks to exchangeable connection modules. Corresponding speaker presets ensure optimum performance and reliability.



Main features

- Output power: 4 × 1000 W / 4 ohms / 100 V / 70 V
- Can be remotely operated and controlled over Fohhn Net
- Extensive DSP, controllable in real time with the Fohhn Audio Soft
- Q-SYS Plugin available
- Temperature controlled, low noise fan
- Auto Power Save for minimum standby power requirements
- Installation size: 2 U / 19"
- Light weight, only 9.8 kg



Available with the following color options



Black

Equipped with the following Fohhn technologies



Fohhn DSP
inside



100 V optional



Auto Power
Save



Power Sharing

Possible input interfaces for this product

Analog

AES/EBU

 Dante™

For detailed information about all Fohhn technologies, color options and connections, please visit www.fohhn.com/en/technologies

Technical data

Physical features

dimensions (w × h × d)	2 U / 19", 485 x 89 x 425 mm
weight	9.8 kg

Electronic features

amplifier technology	Class D
support for AES67	Yes
amplifier outputs	4
DSP routing (matrix)	4 × 4
frequency response	20 Hz – 20 kHz (+/- 0,3dB @ 8 Ohm)
signal/noise ratio	>100 dB (A)
THD+N	0.08 % (1 kHz, 8 ohms, 3 dB below clipping)
dynamic range	>120 dB
password protection	yes
auto power save	adjustable from 1 s to 12 h, or never active
protective circuit	overvoltage protection, overcurrent protection, overtemperature protection, short circuit protection, DC protection, power-on delay, soft start and inrush current limitation
power supply	100 – 240 V AC 50/60 Hz, universal power supply with Power Factor Correction (PFC)
power consumption	Maximum (RMS) 1200 W, idle state 70 W, auto power save 10 W, standby 5 W, power on/off switch / remote power off 2 W
heat dissipation	Maximal 200 W, 680 BTU/h, 172 kcal/h
operating temperature	0 – 40 °C
cooling	temperature-controlled fan
output power	4 × 1000 W / 4 ohms / 100 V / 70 V, 4 × 500 W / 8 ohms (1 kHz, THD+N <1 %)
minimum impedance	3 ohms
input channels	4

Controller	
digital signal processors	2
independent limiters	20
FIR filter	yes
input gain	-80 dB – +12 dB
routing gain	-80 dB – +12 dB
output gain	-80 dB – +12 dB
EQ	8 × 10 fully parametric filters, gain +/-12 dB, frequency 10 Hz – 20 kHz, Q 0.1 – 100
selective 3-band limiting	bass / mid / high
limiter / compressor	8
noise gate	8
delay	4 × 0 – 350 ms (0 – 120 m) outputs, 4 × 0 – 88 ms (0 – 30 m) inputs
X-over	8 × Linkwitz-Riley 4th order (24 dB/octave), high pass 10 Hz – 20 kHz, low pass 10 Hz – 20 kHz
user presets	100
speaker presets	100
system latency	1.2 ms
band-specific time constants	yes
filter technology	80-bit double precision
input	AES/EBU 32 kHz – 96 kHz, 16/24 bit
input DSP processing	yes

Remote control and remote monitoring

remote control	Fohhn Net over RS-485, Fohhn Audio Soft
remote monitoring	temperature, protect, signals, power supply, Fohhn Net, Fohhn Audio Soft
fault message contact	1 × Relais, 2 × UM, 3-pin Phoenix
switching contact	load preset, standby on/off

Display (front)

receive / send LED	remote control, Fohhn-Net
ready LED	blue = Power on, blue flashing = Sign
protect LED	red = Error / Protect / Standby
input LED	4 × input signal LED, white = signal (> -50 dBFS), red = clip (> -3 dBFS)
output LED	4 × output signal LED, white = signal (> -50 dBFS)

Connections and controls

controls	Power on/off Switch
mains connection	1 × PowerCON
fault contact (open/close)	1 × Phoenix 3-pin
switching contact 1 and 2	1 × Phoenix 3-pin
remote power in / out	2 × Phoenix 2-pin
power supply for extern small devices 24 V / 5 W	1 × Phoenix 2-pin
24 V / 5 W power LED	green = on
USB Config	1 × USB-C socket

weight: net weight without optional equipment

heat dissipation: pink noise, 6 dB crest, 1/4 Pmax

Standard input interface (AES/EBU)



Standard input interface (AES/EBU)

inputs	2 × Phoenix 3-pin AES/EBU, 1 × Phoenix 3-pin Fohhn-Net
outputs	2 × Phoenix 3-pin AES/EBU, 1 × Phoenix 3-pin Fohhn-Net
signal inputs	AES/EBU 32 kHz – 96 kHz, 16/24 bit
signal outputs	AES/EBU link out from input
latency	0.0 ms

Input interface AES/EBU XLR



Input interface AES/EBU XLR

inputs	2 × XLR AES/EBU, 1 × etherCON Fohhn-Net
outputs	2 × XLR AES/EBU, 1 × etherCON Fohhn-Net
signal inputs	AES/EBU 32 kHz – 96 kHz, 16/24 bit
signal outputs	AES/EBU link out from input
latency	0.0 ms

Input interface analog XLR



Input interface analog XLR

inputs	4 × XLR analogue, 1 × etherCON Fohhn-Net
outputs	4 × XLR analogue, 1 × etherCON Fohhn-Net
signal inputs	analog, max. level +15 dBu
signal outputs	analog link out from input
frequency response	20 Hz – 20 kHz
THD	<0.003 % typ., <0.0005 % 1 kHz 0 dBu
S/N ratio	>110 dB/A
input impedance	10 k ohm
latency	1.0 ms

Input interface Dante Ultimo (DUC)



Input interface Dante Ultimo (DUC)	
integration in media control	UDP text protocol
support for AES67	Yes
latency	Dante +0.6 ms
inputs	1 × RJ-45 100BASE-T Ethernet, Dante and Fohhn-Net
audio input channels	4
audio link	No
redundancy	No

Output option Speakon



Output option Speakon	
outputs	4 × Speakon

Output option terminal blocks



Output option terminal blocks	
outputs	2 × Phoenix 4-pin
conductor cross-section	max. 6 mm ² flexible, 10 mm ² rigid

Fohhn Audio AG
Großer Forst 15
72622 Nuertingen
Germany

Phone +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
info@fohhn.com

